

# Dimmer

**Typ:** 6523-102-500

**E-nr:** 1360574

**Produkt ID:** 2CKA006512A0340

**GTIN:** 4011395212745



With rotary control, two-way switch and soft-catch. Optimised for dimming of retrofit LED lamps (LEDi). For dimmable Retrofit-LEDs (LEDi). For dimmable Retrofit-LEDs (LEDi) with conventional or electronic transformers. For incandescent lamps, 230 V tungsten halogen lamps, low-voltage halogen lamps with conventional or electronic transformers and dimmable energy-saving halogen lamps. Mix operation of LEDi with conventional loads possible. Via mode switch adjustable between leading edge control and trailing edge control. Low-noise level by MOSFET transistors. With electronic short-circuit protection. With electronic overload protection. With adjustable minimum brightness. Rated voltage: 230 V~, + 10% / - 10% Rated frequency: 50 Hz/60 Hz Nominal power: 2 - 100 W/VA (retrofit LED loads). Nominal power: 10 - 250 W/VA (non-LED loads)

## Teknisk specifikation

### Klassificering

Lämplig för skyddsklass (IP):	IP20
-------------------------------	------

### ETIM Data

Sammansättning:	Modulär enhet för inomhusbrytare
Manövreringsmetod:	Vrid-/Tryckknapp
Antal moduler (modulsystem):	3
Monteringsmetod:	Övrigt
Material:	Plast
Materialkvalitet:	Termoplast
Halogenfri:	Nej

Ytskydd:	Obehandlad
Typ av yta:	Matt
RAL-nummer (liknande):	7035
Slagtålighet (IK):	IK00
Märkspänning:	230 V
Reglerspänning:	220...240 V
Anslutningstyp:	Skruvklämma
Apparatens bredd:	135 mm
Apparatens höjd:	30 mm
Apparatens djup:	25 mm
Kompatibel med Apple HomeKit:	Nej
Kompatibel med Google Assistant:	Nej
Kompatibel med Amazon Alexa:	Nej
Med stöd för IFTTT:	Nej